

Mainlube Superior Maintenance Lubricants Pty Ltd

14 Underwood Ave, Botany NSW, 2017

Ph 02-9700-0880. ACN No. 001 748 876 Fax 02-9700-0881.

STATEMENT OF HAZARDOUS NATURE

Non Hazardous According to Criteria of Worksafe Australia

MATERIAL SAFETY DATA SHEET MAINLUBE 240

IDENTIFICATION

Product Name: Chemical Name: Other Names: Manufacturer's Product Code: UN Number: Dangerous Goods Class Subsidiary Risk[s]: Hazchem Code: EPG NO: Poisons Schedule Number: Toxic and Hazardous Ingredients: Uses: Mainlube 240 Industry Oil and Grease Additive. None Assigned 240 None Assigned None Assigned None Assigned None Assigned None Assigned

None Oil and Grease Additive.

PHYSICAL DESCRIPTION AND PROPERTIES

Colour: Appearance: Form: Boiling Point: Melting Point: Vapour Pressure: Specific Gravity: Volatiles: Evaporation Rate: Vapour Density: Odour: Solubility in Water:

FLASH POINT

Solvent: Lubricant residue: Flammability Limits: Auto ignition Temperature:

OTHER PROPERTIES

Hazardous Ingredients:

Clear. Light Coloured Liquid. Liquid No Data. No Data Not Determined 0.88 at 15.60 Deg C Unknown Not Determined Not Determined Mild Insoluble

Not Applicable 223 °C (PMCC) Unknown

No Data

This material is not known to contain greater than 0.1% of any carcinogen required to be listed under the OSHA Hazard Communication Standard (29CFR 1910.1200). Please note that the chemical identity of some or all of the above hazardous ingredients is confidential business information and is being withheld as permitted by 29CFR 1910.1200 and various State Right to Know Laws.

Page 1 of 3 November, 13

MATERIAL SAFETY DATA SHEET MAINLUBE 240

INGREDIENTS

Chemical Name	CAS Number	Proportion
Mixture	Mixture	



HEALTH HAZARD INFORMATION

HEALTH EFFECTS:

Acute:

Swallowed:	If material is misted or if vapours are generated from heating, exposure may cause irritation of mucous membranes and the upper respiratory tract similar to that observed with mineral oil. Based on data from components or similar materials. Under good industrial hygiene practices where all exposure limits are observed, respiratory irritation should not be a problem.	
Skin:	Not expected to be a primary skin irritant. Based on data from components or similar materials. Prolonged or repeated skin contact as from clothing wet with material may cause dermatitis. Symptoms may include redness, edema, drying, defatting and cracking of the skin.	
Eyes:	Not expected to cause eye irritation. Based on data from components or similar materials.	
Inhaled:	No data available to indicate product or components may be toxic or respiratory sensitisers.	
Chronic:		
LC 50:	No Data	
LD 50:	No Data	
FIRST AID:		
Swallowed:	Do not induce vomiting. If conscious, give two glasses of water. Get immediate medical attention.	
Skin:	Wash with soap and water. Get medical attention if irritation develops. Launder contaminated clothing before reuse.	
Eyes:	Flush with water at least 15 minutes. Get medical attention if eye irritation develops or persists	
Inhaled:	Remove exposed person to fresh air if adverse effects are observed.	

ADVICE TO PHYSICIAN:

Treat symptomatically.

PRECAUTIONS FOR USE

Exposure Standards: The ACGIH TLV for mineral oil mists is 5mg/m³ for a daily 8 hours exposure. Engineering Controls: As for oil mists. Personal Protection: Avoid prolonged or frequently repeated contact. Wash skin thoroughly with soap and water after contact. Use safety glasses and neoprene or nitrile rubber gloves for frequent contact. Flammability: Product is not classed flammable. Flash Point greater than 190°C Product may support combustion. Do not store with strong oxidants.

MATERIAL SAFETY DATA SHEET MAINLUBE 240

Page 3 of 3

SAFE HANDLING INFORMATION

Storage and Transport:	Keep containers closed when not in use.	
Storage Temperature:	Material is normally stable at moderately	
elevated	temperatures and pressures.	
UN Class:	None Assigned	
Packaging Group :	None Assigned None Assigned	
UN Number:		
EPG Number:	None Assigned	
Correct Shipping Name:	Industry Oil and Grease Additive.	
Spills and Disposals:	Personal protective equipment must be worn. Ventilate	
	area if spilled in confined space or other poorly	
	ventilated areas. Prevent entry into sewers and	
	waterways. Pick up free liquid for recycle and/or disposal. Residue liquid can be absorbed on inert material. Check under Transportation and Labelling (DOT/CERCLA) and other regulatory Information Section (SARA) for hazardous substances to determine	
Fire/Evaluation Hazard	regulatory reporting requirements for spills. Not Known	
Fire/Explosion Hazard:		
Decomposition Products:	Smoke, carbon monoxide, aldehydes and other	
	products of incomplete combustion.	
Hazchem Code:	None Assigned	
Extinguishant:	CO ₂ dry chemical, alcohol foam. Water can be used to cool and protect exposed material.	

DANGER OF VIOLENT REACTION OR EXPLOSION: No

Protective Clothing;	Refer to Personal Protection/
Appropriate Measures;	No Data
Evacuate;	No Data

OTHER INFORMATION:

No other health hazards known. Unusual Fire & Explosion Hazards: Toxic fumes, gases or vapours may evolve on burning.

CONTACT POINT:

Mr Steve Simmonds Mainlube Superior Maintenance Lubricants Pty Ltd. 14 Underwood Ave, Botany. NSW, 2019, Australia Ph 02-9700-0880. Fax 02-9700-0881. Mob 0412-644-244.

24 Hour Emergency Tel No. Above Mobile Phones

Emergency Services

Dial 000

We believe the statement, technical information and recommendation contained herein are reliable, but they are given without warranty or guarantee of any kind, express or implied, and we assure no responsibility for any loss, damage, or expense, direct or consequential, arising out of their use.