



Mainlube Superior Maintenance Lubricants Pty Ltd

14 Underwood Ave, Botany NSW, 2017

Ph 02-9700-0880.

ACN No. 001 748 876

Fax 02-9700-0881.

STATEMENT OF HAZARDOUS NATURE

Hazardous According to Criteria of Worksafe Australia

MATERIAL SAFETY DATA SHEET MAINLUBE 440

IDENTIFICATION

Page 1 of 3
Nov-13

| | |
|----------------------|--|
| Product Name; | Mainlube 440 Aerosol Cleaner Degreaser |
| Chemical Name; | Dichlorofluoroethane |
| Manufacturer's Code; | 440 |
| UN Number; | 1950 Aerosols |
| DG Class; | 2.2 Aerosol, Non Flammable N.O.S. |
| Packaging Group; | 203, Y203 |
| Subsidiary Risk[s]; | none |
| Hazchem Code; | 2 Y |
| EPG NO; | 2D1 |
| Poisons Schedule | None assigned. |
| Uses; | As a spray-on degreaser and cleaner Use as directed on the product label. |

PHYSICAL DESCRIPTION AND PROPERTIES

| | |
|-------------------|------------------------------------|
| Appearance; | Colourless Liquid |
| Boiling Point; | 89.6°C |
| Melting Point; | Not applicable. |
| Vapour Pressure; | 10.02psia @ 70°F |
| Volatiles; | 100 % |
| Evaporation Rate; | >1 Compared to Ether+1. |
| Odour; | Ethereal and faint sweetish odour. |
| Vapour Density; | 4.1 [air = 1] |
| Weight per ml; | 1.16 @ 70°F] |

FLASH POINT;

| | |
|-------------------------------|---------|
| Solvent | None |
| Flammability Limits: | No Data |
| Auto ignition Temperature; | 550°C. |

INGREDIENTS

| Chemical Name | CAS Number | Proportion |
|----------------------------|---------------|------------|
| Dichlorofluoroethane | No Data | 30-60%. |
| CO ₂ Propellant | 124-38-9 | 30-60%. |
| Proprietary Additives | None Assigned | 2-5% |

440MSDS

MATERIAL SAFETY DATA SHEET MAINLUBE 440

Page 2 of 3
Nov-13

HEALTH HAZARD INFORMATION

Acute;

Inhaled; Both solvent and propellant act as simple asphyxiants, and at high vapour levels may cause loss of consciousness and death from oxygen deprivation.

Exposure Limits Solvent

Acute Inhalation Albino Rats (Sprague-Dawley) 4 hr-LC50'
62,000 ppm.

Exposure Limits Propellant; [NOHSC]

TLV-TWA; Carbon dioxide 5,000 ppm, 9,000 mg/m³
TLV-STEL; Carbon dioxide 30,000 ppm, 54,000 mg/m³
[NOHSC] - National Occupational Health and Safety Commission
[Worksafe Australia]

Swallowed; Similar symptoms as for inhalation. Discomfort due to the volatility of the solvent would be expected.

Non Toxic; > 5 grams per Kg Body weight,
Cardiac sensitisation threshold, 20,000ppm.

Skin; If sprayed directly onto the skin, the solvent may have a degreasing effect which might lead to irritation.

Eyes; If sprayed directly into the eyes., solvent will irritate before evaporating.

Chronic; No data.

FIRST AID; If poisoning occurs, contact a doctor or Poisons Information Centre.

Swallowed; If swallowed, do NOT induce vomiting. Give a glass of water. Do NOT give stimulants

Skin; If skin contact occurs, remove contaminated clothing and wash skin thoroughly.

Eyes; If in eyes, hold eyes open, flood with water for at least 15 minutes and see a doctor.

Inhaled; Remove from exposure. If breathing has stopped, apply artificial respiration. In severe cases, obtain medical attention. Do NOT give stimulants or adrenalin (epinephrine).

FIRST AID FACILITIES RECOMMENDED;

Eye wash. Hand wash basin.

ADVICE TO DOCTOR

Product is an aerosol containing non-toxic Cleaner Degreaser
The solvent and the propellant can act as simple asphyxiants.
treat symptomatically. Contact Poisons Information Centre.

HAZARD INFORMATION OTHER PROPERTIES;

Solvent evaporates rapidly to no residue.

ENGINEERING CONTROLS;

Ensure adequate ventilation. Avoid using in enclosed spaces. Consider local mechanical exhaust/extraction to keep airborne contamination below TLV.

MATERIAL SAFETY DATA SHEET MAINLUBE 440

Page 3 of 3
Nov-13

PERSONAL PROTECTION;

Do not spray directly into eyes, mouth or nose. Avoid spraying directly onto the skin. Do not smoke while using this product; solvent vapours drawn into lighted cigarettes will decompose to form toxic products of combustion.

Personal protection to be selected from those recommended below, as appropriate to mode of use, quantity handled and degree of hazard;

Self contained breathing apparatus, Supplied-air hood, Face shield or safety glasses, Gloves, rubber or plastic, Overalls.

SAFE HANDLING INFORMATION

STORAGE ADVICE;

Store in a cool, <50°C, well ventilated place, out of reach of children. Large quantities should be stored in a dangerous goods store. Store out of direct sunlight. No smoking or welding. Prevent vapours from collecting in enclosed spaces. Protect from physical damage. Attend to leaking cans immediately; avoid secondary accidents.

SPILLS AND DISPOSALS;

Leaking cans should be carried to a safe, open area for atmospheric evaporation. Ventilate area to dispel any residual vapours.

FIRE/EXPLOSION HAZARD; Yes, contents under pressure

Solvent vapour/air mixture may be decomposed by very high temperatures to form toxic products. Cans may rupture violently if involved in a fire. Evacuate Immediate Area.

DECOMPOSITION PRODUCTS;

Carbon Dioxide, Hydrochloric Acid, Hydrofluoric Acid, and Carbonyl Halides such as Phosgene. Solvent incompatible with finely divided active metals, alkali earth metals. (May cause strong exothermic reaction.) Strong oxidising agents and some desiccants may react. Solvent vapour/air mixture may be decomposed at very high temperatures eg. by welding or other high temperature source.

HAZCHEM CODE; 2 Y
Extinguishant; Water fog or fine water spray.

CONTACT POINT:

Mr Steve Simmonds
Mainlube Superior Maintenance Lubricants Pty Ltd.
14 Underwood Ave, Botany. NSW, 2019, Australia
Ph 02-9700-0880. Fax 02-9700-0881.
Mob 0412-644-244.

24 Hour Emergency Tel No. Above Mobile Phones

Emergency Services Dial 000

We believe the statement, technical information and recommendation contained herein are reliable, but they are given without warranty or guarantee of any kind, express or implied, and we assure no responsibility for any loss, damage, or expense, direct or consequential, arising out of their use.