



## Mainlube Superior Maintenance Lubricants Pty Ltd

189-191 Botany Road Waterloo, NSW, 2017

Ph 02-9310-3433.

ACN No. 001 748 876

Fax 02-9310-3503.

### STATEMENT OF HAZARDOUS NATURE

Non Hazardous According to Criteria of Worksafe Australia

## MATERIAL SAFETY DATA SHEET MAINLUBE 500

### IDENTIFICATION

Page 1 of 3  
Nov-13

<b>Product Name;</b>	Mainlube 500 Primer Paint
<b>Chemical Name:</b>	Primer Paint.
Other Names:	Not Applicable
Manufacturer's Product Code:	500.
UN Number:	Mixture, None Assigned
Dangerous Goods Class	Not Applicable
Subsidiary Risk[s]:	No Data.
Hazchem Code:	None Assigned
EPG NO:	None Assigned
Poisons Schedule Number:	None Assigned
Uses:	Etch Primer

### PHYSICAL DESCRIPTION AND PROPERTIES

Colour:	Red Brown liquid.
Appearance	Mobile Liquid with slight Ammonia Smell.
Form:	Liquid
Boiling Point:	100°C Water.
Melting Point:	0°C Water.
Vapour Pressure:	17 Hg (1 Atm) @ 20°C Water.
Specific Gravity:	(Water=1) @ room temperature, approx 1.33-1.8.
Solids:	60-70%.
Evaporation Rate:	As Water.
Vapour Density:	No Data.
Odour:	Slight Ammonia Smell.
Solubility in Water: (by weight %)	100% @ 25°C.

### FLASH POINT

Solvent:	Non Flammable.
Flammability Limits :	Non Flammable.
Auto ignition Temperature:	Non Flammable

### OTHER PROPERTIES

# MATERIAL SAFETY DATA SHEET MAINLUBE 500

Page 2 of 3  
Nov-13

## INGREDIENTS

Chemical Name	CAS Number	Proportion
Proprietary Non Hazardous Formulation		

## HEALTH HAZARD INFORMATION

### HEALTH EFFECTS:

#### Acute:

Swallowed: Not considered toxic, No significant health effects have been found, However if symptoms occur seek Medical assistance.

Skin: Temporary Irritant to Skin.

Eyes: Temporary Irritant to eyes

Inhaled: No Data Available.

#### Chronic:

No Data

LC 50: No Data

LD 50: >5000 mg/kg

#### FIRST AID:

Swallowed: Rinse mouth thoroughly with water thoroughly. Give water to drink.

Skin: Wash effected areas with water immediately to prevent paint adhering.

Eyes: Immediately irrigate with copious quantity of water for at least 15 minutes. Eyelids to be held open.

Inhaled: Remove victim from exposure, Allow patient to assume most comfortable position and keep warm. If breathing laboured Seek medical attention.

#### FIRST AID FACILITIES:.

#### ADVICE TO PHYSICIANS:

Treat symptomatically based on judgement of doctor and individual reactions of patient.

#### PRECAUTIONS FOR USE:

Exposure Standards: No exposure standard has been established for this product

Engineering Controls: If applying by compressed air spray gun, maintain concentration below recommended exposure limit for air born particulate matter.

Personal Protection: Overalls or similar protective apparel. Safety glasses, goggles or face shield as appropriate

Flammability: The product is considered non-combustible.

## SAFE HANDLING INFORMATION

Storage and Transport: Store in well ventilated area. Store in a cool, dry place. Keep from freezing, material may coagulate, Maximum storage temperature <50 °C Keep container well sealed.

Storage Temperature: 1-49°C

UN Class: None Assigned

Packaging Group: Not Applicable

# MATERIAL SAFETY DATA SHEET MAINLUBE 500

## SAFE HANDLING INFORMATION CONTINUED

Page 3 of 3  
Nov-13

UN Number: None Assigned)  
UN Number: None Assigned)  
EPG Number: None Assigned  
Correct Shipping Name: Water Based Paint  
Spills and Disposals: Keep spectators away, Floor may be slippery, use care to avoid falling. Contain spill immediately, use sand, sawdust, etc. Transfer liquid and dyking material to containers for disposal. Prevent spills and cleaning runoff from entering sewers.  
Fire/Explosion Hazard: This material is considered stable, However avoid temperatures above 200°C, the onset of polymer decomposition, Thermal decomposition is dependent on time and temperature.  
Decomposition Products: Thermal decomposition may yield Acrylic Monomers.  
Hazchem Code: No Data  
Extinguishant: In case of fire, use extinguisher appropriate for burning material.

## DANGER OF VIOLENT REACTION OR EXPLOSION:

No

Protective Clothing; Fire fighters should wear full protective clothing including self contained breathing apparatus.  
Appropriate Measures; No Data.  
Evacuate; No Data.

## OTHER INFORMATION:

*There are no known materials that are incompatible with this product.*

## ENVIRONMENTAL COMMENTS:

Mobility This material is water soluble. It may contaminate water, soils or sediments.  
Degradability This product is expected to biodegrade.  
Accumulation This product is not expected to bioaccumulate

## CONTACT POINT:

Mr Steve Simmonds, Mr Rob Simmonds,  
Mainlube Superior Maintenance Lubricants Pty Ltd.  
189-191 Botany Road Waterloo, NSW, 2017, Australia  
Ph 02-9310-3433. Fax 02-9310-3503.  
Mob 0412-644-244, Mob 0411-243-150.

## 24 Hour Emergency Tel No. Above Mobile Phones

### Emergency Services

Dial 000

*We believe the statement, technical information and recommendation contained herein are reliable, but they are given without warranty or guarantee of any kind, express or implied, and we assure no responsibility for any loss, damage, or expense, direct or consequential, arising out of their use.*