



365

DESCRIPTION:

Heavy Duty Water Resistant Open Grease. Water and corrosion resistant with excellent shock loading and boundary lubrication capabilities. Evaporative carrier leaves a tough wear resistant protective coating. Operating Temp Range - 15°C to 150°C NLGI # 3.5. Available as Bulk or 300 gm Chalk Tube and Aerosol as 465.

CHARACTERISTICS:

Non Hardening Formula

Mainlube 365 is designed for lubrication of medium to heavy duty open gears. Inorganic couplers are reacted with an organo clay thickener then combined with Mainlube 365's synthetic Polybutene base oil. The organo clay thickener lets 365 perform well at elevated temperatures and is extremely resistant to shear and drying out. 365 Contains a high percentage of solids, these supplements prevent creeping and squeeze out of the load zone providing essential boundary lubrication. Mainlube 365's evaporative carrier leaves a tough, shear, wear, water and heat resistant protective coating.

Protects Slow Moving Heavily Loaded Equipment.

The wiping and sliding action of Open Gears requires special lubrication. Open Gear's transmit considerable amounts of energy and exert sliding forces upon themselves when under operational loads. 365 Extends protection for heavy loads showing excellent adhesion with minimal throw off.

Corrosive Resistant

365's Tough wear resistant protective coating provides good corrosion protection and is suitable for application in sea water, brine, chemical and corrosive atmospheres. 365 Will provide long term protection reducing oxidation, corrosion, rust rigidity and failure.

Extreme Tenacity

Mainlube 365 has extreme tenacity and spreads over metal surfaces providing a liquid pressure resisting wedge keeping metal apart preventing, scuffing, galling, clawing, scoring, rippling and pitting.

Environmentally Friendly

Mainlube 365 contains no hazardous materials or heavy metals. In the past the most successful open gear greases have used Barium thickeners. Barium is a heavy metal and has been banned by the EPA (Environmental Protection Agency) in the USA. Mainlube 365 uses state of the art technology which exceeds the performance of the old Barium products without containing any hazardous materials or heavy metals.

APPLICATION

Mainline 365 has unlimited applications in open gear driven equipment like; ski lifts, cable ways, timber drags, rail pulleys, earth moving equipment, water pumps, wind mills, hoists, cranes, walking cranes and any open gear driven equipment. Application can be by bulk, chalk tube applicator or aerosol as Mainlube 465.



365

SPECIFICATIONS:

TEST

**ASTM
TEST METHOD**

**TEST
RESULT**

MAINLUBE SUPERIOR MAINTENANCE LUBRICANTS PTY LIMITED
ACN 001-748-876 SYDNEY AUSTRALIA

DISTRIBUTED BY:

SB365 -2 BAAI