



# 510

## **DESCRIPTION:**

**Battery Terminal And Metal Protector. Non toxic penetrating anti-rust coating, suitable for all metals. Resistant to light abrasion and knocking. Protects battery terminals, tools, dies, taps, vehicle internal panels and farm implements. Use as a plant pruning sealant. Remove with mineral spirits. Available in Bulk and Aerosol as 410.**

## **CHARACTERISTICS:**

### **Corrosion Coating**

Mainlube 510 is a heavy duty all purpose anti-corrosion coating.

510's Coating system when applied will penetrate and suppress any existing corrosion, forming a protective layer that seals out further oxidation caused by moisture, chemicals, weathering or fumes.

### **Abrasion Resistant**

510's Coating is resistant to minor knocking and abrasion, will not crack or peel.

### **510 Is Ideal For Protecting:**

Ploughshares	Tools, Dies & Moulds	Lawn mowers
Spare Parts	Snowploughs	Farm Implements
Military Stores	Marine Equipment	Ski Resort Equipment
Crushers	Seasonal Production	Grader Blades
Portable Conveyors	Plant Equipment	Machinery
Hammermills	Cannery Equipment	Trailers
Aircraft Service Equipment	Construction Equipment	Battery Terminals

### **Advantages:**

510 has excellent adhesion allowing less man hours cleaning metal before application. Exceptional bonding and coating properties mean usually a single coat will provide long term protection.

510 Will not easily damage in normal storage, reducing the need to reapply.

Easy application no special skills .

Good coverage rate 5 square meters per can.

Simple removal, just wipe with mineral spirit.

Non toxic, no residues, or irritating fumes 510 can be used in confined areas.

Good long term protection exceeds 24 months under good storage conditions.

No special mixing or preparation.



# 510

## **HOW TO APPLY:**

### ***Ease Of Application:***

For best results long term, ensure metal is degreased and clean before applying 510. Mainlube 510 just spray, paint or dip on as required, reduces wastage, and the need for skilled labour and/or special equipment.

### ***Extensive Coverage:***

One coating of Mainlube 510 is sufficient for normal use.

### ***Simple Removal:***

Rags soaked in Mineral Spirit will remove Mainlube 510 from metal parts. The ease of removal eliminates mess and clean-up-time.

### ***Safety In Use:***

Mainlube 510 is free of noxious, toxic or irritating fumes and gases. This allows application in enclosed or confined spaces without any danger to personnel.

## **SPECIFICATIONS:**

Colour	Clear Brown
Practical Coverage	Approx. 15 sq. m/litre
Drying Time @ 20 °C to 28 °C	
To Touch	2-4 hours (mixture concentration changes (drying time))
Dry	48- hours
Clean Up/Removal	Mineral Spirits

MAINLUBE SUPERIOR MAINTENANCE LUBRICANTS PTY LIMITED  
ACN 001-748-876 SYDNEY AUSTRALIA

**DISTRIBUTED BY:**

**SB510-2 AHAB**